


**PRELIMINARY DETAIL**  
NOT FOR FINAL CONSTRUCTION




**TYPICAL REINFORCED RETAINING SECTION**

(NO SCALE)

- A. Wall height above grade (varies by design)
- B. Wall buried beneath grade (varies by design)
- C. Leveling pad depth (varies by design)
- D. 1/2" setback per 6" course (5')
- E. Crushed stone leveling pad
- F. Foundation soil compacted to 95% max. dry density
- G. Drainstone (ASTM #57, min. 12" behind wall)
- H. 4" corrugated perforated drain pipe
- I. Geogrid (lengths and vertical placement per design)
- J. Min. 3.5 oz. non-woven geotextile fabric (recommended)
- K. Finish grade to drain away from the wall

This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site.

DRAWN BY: BOB/CARISSA	TITLE:	<b>BELVEDERE TYPICAL REINFORCED RETAINING WALL</b>	 <b>HIGH FORMAT</b> <sup>®</sup>
APPROVED BY:			
DATE: 11/15/2021			
SHEET NO.: 1 OF 1	DRAWING TITLE: Belvedere Typical Cross Section.dwg		05481 US 31 SOUTH, CHARLEVOIX, MI 49720 877-777-6558 • highformat.com